



Image shown may not represent actual configuration

## C13 High Ambient Enclosures

50 Hz / 60 Hz

These high ambient, factory installed enclosures incorporate internally mounted residential level silencers, designed for safety and aesthetic value on integral fuel tank base or optional dual wall integral fuel tank base for total fluid containment. These enclosures are of extremely rugged construction to withstand exposure to the elements and provide weather protection.

### Features

#### Robust / Highly Corrosion Resistant Construction

- Factory installed on integral fuel tank base
- Environmentally friendly, polyester powder baked paint
- 1.6mm (0.063in) galvanized steel
- All round overhanging base to protect enclosure
- High-grade engineering thermoplastic corner posts for protection
- Integral lifting frame
- Compression door latches giving solid door seal
- Zinc plated or black coated stainless steel fasteners
- Internally mounted super critical exhaust silencing system

#### Excellent Access

- Large cable entry area for installation ease
- Accommodates rear mounted breaker and control panel
- Double doors on both sides
- Vertically hinged doors with solid bar door stays to hold doors open at 135° rotation
- Lube oil and coolant drains pipes to exterior of enclosure and terminated drain valves
- Radiator fill cover

#### Security and Safety

- Lockable access doors which give full access to control panel and breaker
- Cooling fan and battery charging alternator fully guarded
- Fuel fill, oil fill and battery can only be reached via lockable access
- Externally mounted emergency stop button
- Designed for spreader-bar lifting to ensure safety
- Control panel viewing window
- Stub-up area is rodent proof

#### Options

- Caterpillar Yellow or white paint
- Integral dual wall fuel tank base for total fluid containment (fuel, oil and coolant)

## Enclosure Package Operating Characteristics

| Model        | kVA | ekW | SB/PP | Sound Pressure Levels dBA |           |            |           | Air Flow Rate |       | Ambient Capability at 100% Load* |     |
|--------------|-----|-----|-------|---------------------------|-----------|------------|-----------|---------------|-------|----------------------------------|-----|
|              |     |     |       | 1m (3.3 ft)               |           | 7m (23 ft) |           | m³/s          | cfm   | °C                               | °F  |
|              |     |     |       | 75% Load                  | 100% Load | 75% Load   | 100% Load |               |       |                                  |     |
| <b>50 Hz</b> |     |     |       |                           |           |            |           |               |       |                                  |     |
| DE400E0      | 350 | 280 | PP    | 81                        | 83        | 73         | 74        | 5.6           | 11866 | 54                               | 129 |
|              | 400 | 320 | SB    | 82                        | 84        | 73         | 76        | 5.6           | 11866 | 54                               | 129 |
| DE450E0      | 400 | 320 | PP    | 82                        | 84        | 73         | 76        | 5.6           | 11866 | 49                               | 120 |
|              | 450 | 360 | SB    | 83                        | 85        | 74         | 77        | 5.6           | 11866 | 49                               | 120 |
| <b>60 Hz</b> |     |     |       |                           |           |            |           |               |       |                                  |     |
| DE350SE0     | 400 | 320 | PP    | 83                        | 84        | 75         | 76        | 7.9           | 16739 | 56                               | 133 |
|              | 438 | 350 | SB    | 83                        | 85        | 75         | 76        | 7.9           | 16739 | 57                               | 135 |
| DE400SE0     | 438 | 350 | PP    | 83                        | 85        | 75         | 76        | 7.9           | 16739 | 52                               | 126 |
|              | 500 | 400 | SB    | 84                        | 86        | 75         | 77        | 7.9           | 16739 | 51                               | 124 |

\*Ambient capability measured with the Cat extended life coolant at sea level.



Approximate weight of enclosure package: 4780 kg (10,538 lb). Exact weight is dependent on options. Enclosure weight includes: high ambient enclosure, exhaust system, base and generator set.

[www.cat.com/electricpower](http://www.cat.com/electricpower)

©2016 Caterpillar  
All rights reserved.

ENCSA70  
ENCSA71

LEHE0445-01 (11/16)

Materials and specifications are subject to change without notice.  
CAT, CATERPILLAR, their respective logos ACERT, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

**C13 ACERT**  
**320 ekW/ 400 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor**

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION



**C13 ACERT**  
**320 ekW/ 400 kVA**  
**50 Hz/ 1500 rpm/ 400 V**

Image shown may not reflect actual configuration

**Metric English**

| Package Performance                             |         |     |
|---|---------|-----|
| Genset Power Rating with Fan @ 0.8 Power Factor | 320 ekW |     |
| Genset Power Rating                             | 400 kVA |     |
| Aftercooler (Separate Circuit)                  | N/A     | N/A |

| Fuel Consumption   |           |             |
|--------------------|-----------|-------------|
| 100% Load with Fan | 82.0 L/hr | 21.7 gal/hr |
| 75% Load with Fan  | 61.8 L/hr | 16.3 gal/hr |
| 50% Load with Fan  | 43.2 L/hr | 11.4 gal/hr |
| 25% Load with Fan  | 25.8 L/hr | 6.8 gal/hr  |

| Cooling System <sup>1</sup> |        |         |
|-----------------------------|--------|---------|
| Engine Coolant Capacity     | 14.2 L | 3.8 gal |

| Inlet Air                                |                          |           |
|--|--------------------------|-----------|
| Combustion Air Inlet Flow Rate           | 22.7 m <sup>3</sup> /min | 802.1 cfm |
| Max. Allowable Combustion Air Inlet Temp | 44 ° C                   | 111 ° F   |

| Exhaust System                                  |                          |                |
|---|--------------------------|----------------|
| Exhaust Stack Gas Temperature                   | 506.0 ° C                | 942.8 ° F      |
| Exhaust Gas Flow Rate                           | 62.2 m <sup>3</sup> /min | 2197.3 cfm     |
| Exhaust System Backpressure (Maximum Allowable) | 10.0 kPa                 | 40.0 in. water |



**C13 ACERT**  
320 kW/ 400 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor

Rating Type: PRIME

Fuel Strategy: LOW FUEL CONSUMPTION

| Heat Rejection                              |        |               |
|---|--------|---------------|
| Heat Rejection to Jacket Water              | 133 kW | 7549 Btu/min  |
| Heat Rejection to Exhaust (Total)           | 313 kW | 17789 Btu/min |
| Heat Rejection to Aftercooler               | 66 kW  | 3775 Btu/min  |
| Heat Rejection to Atmosphere from Engine    | 54 kW  | 3056 Btu/min  |
| Heat Rejection to Atmosphere from Generator | 24 kW  | 1348 Btu/min  |

| Alternator <sup>2</sup>                     |          |
|---|----------|
| Motor Starting Capability @ 30% Voltage Dip | 898 skVA |
| Current                                     | 577 amps |
| Frame Size                                  | LC6124C  |
| Excitation                                  | AR       |
| Temperature Rise                            | 125 ° C  |

| Emissions (Nominal) <sup>3</sup> |                           |             |
|----------------------------------|---------------------------|-------------|
| NOx                              | 2616.4 mg/Nm <sup>3</sup> | 5.1 g/hp-hr |
| CO                               | 710.0 mg/Nm <sup>3</sup>  | 1.4 g/hp-hr |
| HC                               | 2.7 mg/Nm <sup>3</sup>    | 0.0 g/hp-hr |
| PM                               | N/A                       | N/A         |

**DEFINITIONS AND CONDITIONS**

1. For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.
2. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40° C ambient per NEMA MG1-32.
3. Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

**C13 ACERT  
320 ekW/ 400 kVA/ 50 Hz/ 1500 rpm/ 400 V/ 0.8 Power Factor**

**Rating Type: PRIME**

**Fuel Strategy: LOW FUEL CONSUMPTION**

**Applicable Codes and Standards:**

AS1359, CSA C22.2 No100-04, UL142,UL489, UL869, UL2200,  
NFPA37, NFPA70, NFPA99, NFPA110, IBC, IEC60034-1, ISO3046, ISO8528,  
NEMA MG1-22,NEMA MG1-33, 72/23/EEC, 98/37/EC, 2004/108/EC

Note: Codes may not be available in all model configurations. Please consult your local Cat Dealer representative for availability.

**PRIME:**Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated ekW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

**Ratings** are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions

**Fuel Rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

[www.Cat-ElectricPower.com](http://www.Cat-ElectricPower.com)

Performance No.: EM0432-02

Feature Code: C13DE21

Generator Arrangement: 4215198

Date: 05/26/2015

Source Country: CHINA

The International System of Units (SI) is used in this publication. CAT, CATERPILLAR, their respective logos, ADEM, EUI, S•O•S, "Caterpillar Yellow" and the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.